



NEW
STRAW CHOPPER MOUNTED
ON FRONT HITCH

EM-300-F

The EM 310-F mounted straw chopper with 3 m³ capacity has been designed to chop and distribute any type of fodder according to different cutting systems.

We have designed a particularly lightweight equipment for farms with difficult access, guaranteeing a high degree of maneuverability in any environment.

It is fitted with a hydraulically driven mobile floor with chains and crossbars.



HYDRAULIC DRIVE OF TURBINE
AND CROSSBEATERS



LONG CHOPPER' BOX

300° ADJUSTABLE CHUTE



- 3.5 m³ capacity
- Empty weight 1.880 kg
- Maximum flow rate 120 litres/min
- Crossbeater diameter 590 mm
- 300° adjustable distribution chute
- MAXI dimensions for rectangular bales 1.2 m x 1.2 m x 2.5 m length
- MAXI dimensions for round bales 1.8 m diameter x 1.2 m wide
- Hydraulic drive of the turbine and crossbeater
- Hydraulically driven chain mobile floor with speed control in the forward direction
- Electric remote controls
- Indicator light for crossbeater's jam



(*) The hydraulic installation involves the installation of a hydraulic hose of 1-1/4" to the oil tank of the telescopic loader. Both this installation and the assembly of the straw chopper to the telescopic loader will be carried out by the dealer or, where appropriate, the end customer. TATOMA will provide all the necessary information to run the installation.



INGENIERÍA Y MONTAJES MONZON, S.L.
Pol. Industrial Paúles, parc 53-55 - 22400 Monzón
(Huesca), ESPAÑA

Tel.: (+34) 974 401 336 - Fax: (+34) 974 400 670

inmosa@grupopotatoma.com
www.grupopotatoma.com

TATOMA
GRUPO



Sistema de
Gestión
ISO 14001:2015
ISO 9001:2015
ISO 45001:2018

www.tuv.com
ID 9105024614



CE